

MATERIAL SAFETY DATA SHEET

SECTION 1-COMPANY IDENTIFICATION

CHANGQING PROPPANT CORPORATION

12946 S. Dairy Ashford Road, Suite 410, Sugar Land, TX 77478

EMERGENCY CONTACT: 1 (832) 532-7390

SECTION 2-PRODUCT IDENTIFICATION

TRADE NAME: CQHsp™ (all mesh sizes)

SYNONYM(S): Ceramic proppant, Semi-Crystalline Alumina Silicate Inter

CHEMICAL FAMILY: Aluminosilicate

SECTION 3 - COMPONENT INFORMATION

INGREDIENTS CAS NUMBER CONCENTRATION CLASSIFICATION R-PHRASES

Mullite 1302-93-8 >70% Not Classified Not assigned

SECTION 4-PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT: N/A°F

MELTING POINT: 4000°F (estimated) SPECIFIC GRAVITY: 3.5 (H2O = 1)

pH: N/A

BULK DENSITY: 118 lbs/cu.ft.

VAPOR PRESSURE: N/A mm Hg % VOLATILE BY WEIGHT: N/A

VAPOR DENSITY: N/A (Air=1) EVAPORATION RATE: N/A (Butyl Acetate=1)

SOLUBILITY IN WATER: Insoluble

APPEARANCE/ODOR: Odorless brown to dark green to black spheres

VOLATILE ORGANIC COMPOUNDS (VOC): 0 lbs/gal (EPA Reference Methods 24)

SECTION 5-FIRE-FIGHTING MEASURES

SPECIAL FIRE FIGHTING PROCEDURES:

This material is not combustible, un-flammable and un-volatile. Use extinguishing agent suitable for type of surrounding fire.

ESTIMATED EXPLOSIVE LIMITS (% By volume in air): LEL: N/A;

UEL: N/A;

FLASH POINT: N/A;

UNUSUAL HAZARDS: N/A



SECTION 6 - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

No Special procedures are required for clean-up of spills or leaks of this material. Caution should be exercised regarding personal safety and exposure to the spilled material, the material's nature could cause reduced traction. Persons should take care so as not to slip.

SECTION 7 - HANDLING AND STORAGE

HANDLING: Do not create dust. Use personal protective equipment. Refer to section 8 for personal

protective equipment.

STORAGE: Store dry in closed container to reduce dust.

SECTION 8 - EXPOSURE CONTROLS/PROTECTION DURING USE

EXPOSURE LIMITS:

INGREDIENTS OSHA PEL-TWA ACGIH-TWA TLV Corundum 15 mg/m3 (total) 10 mg/m3 (total)

5 mg/m3 (respirable) 3 mg/m3 (resp)

Mullite 15 mg/m3 (total) 10 mg/m3 (total)

5 mg/m3 (respirable) 3 mg/m3 (resp)

ENGINEERING CONTROL MEASURES:

Exposure to this material may be controlled in a number of ways. The measures appropriate for a particular worksite depend on how the material is used and the potential for exposure. Use of the basic principles of industrial hygiene will enable safe handling of the material.

RESPIRATORY: An applicable NIOSH/MSHA or equivalent approved respirator should be worn

where airborne exposures may exceed OSHA/ACGIH permissible air

concentrations.

EYE PROTECTION: Wear safety glasses or chemical goggles to prevent eye contact. Do not wear

contact lenses when working with this substance unless protected

under full coverage goggles.

CLOTHING/GLOVES: Gloves are optional to reduce abrasion.

WORK HYGIENE PRACTICES: Handle in accordance with good personal hygiene and safety practices.

VENTILATION: Provide sufficient (general and/or local exhaust) ventilation to maintain

exposure below permissible air concentrations.



SECTION 9 - FIRST AIDMEASURES

INHALATION:

Remove affected person from source of exposure. Get medical attention if irritation occurs.

INGESTION:

Seek medical attention if large quantities are ingested.

EYE CONTACT:

Immediately flush eyes with large amounts of water, lifting the lower and upper lids occasionally. If irritation is present after washing, get medical attention.

SKIN CONTACT:

Wash the affected area with soap and water. Get medical attention if irritation occurs.

SECTION 10 - STABILITY AND REACTIVITY

REACTIVITY: Minimal STABILITY: Stable

INCOMPATIBLE MATERIALS: Chlorine Triflouride.

SECTION 11 - HEALTH HAZARD INFORMATION

INHALATION:

Inhalation of dusts may cause respiratory tract irritation. Repeated or prolonged breathing of particles of respirable size may cause severe respiratory disease. However, this product contains few particles of respirable size. The amount of dust due to breakdown during shipment and intended use and handling is not expected to exceed applicable exposure limits.

EYE CONTACT: Airborne dust may cause irritation to eyes.

SKIN CONTACT: Prolonged contact with a skin may cause irritation.

HMIS RATING: HEALTH 1 (slight) FLAMMABILITY 0 (minimal) REACTIVITY 0 (minimal)

SPECIAL PROTECTION: (See section 8)

SECTION 12 - TOXICOLOGICAL INFORMATION

ACUTE EFFECTS

Coughing and throat irritation are early symptoms of excessive exposure. May cause irritation to the respiratory system, lungs and skin. May also irritate eyes.

CHRONIC EFFECTS:

Chronic exposure in excess of established human exposure levels can cause severe respiratory disease.



SECTION 13 - ECOLOGICAL INFORMATION

This product poses no significant environmental contamination impact during expected use, handling, and proper disposal.

SECTION 14 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL: Disposal must be at an approved waste disposal facility and in accordance with applicable Federal, State and Local laws and regulations. Contact the district Director of the Environmental Protection Agency and/or state regulatory agency for appropriate requirements.

SECTION 15 - TRANSPORTATION INFORMATION

DOT SHIPPING DESCRIPTION Not Restricted ICAO/IATA Not Restricted RID/ADR Not Restricted CAN Not Restricted IMO Not Restricted

UN NO. N/A

SECTION 16 - REGULATORY INFORMATION

TOXIC SUBSTANCE CONTROL ACT (TSCA) STATUS: All chemicals in this product are listed, automatically included, or are exempt from listing on the TSCA Inventory.

SARA TITLE III: Section 302: None

Section 312: None Section 313: None

CERCLA REPORTABLE QUANTITY: None

CLEAN AIR AMENDMENTS-HAZARDOUS AIR POLLUTANTS (HAPS): None

CALIFORNIA STATE PROPOSITION 65: N/A

SECTION 17 - OTHER INFORMATION

N/A